



Constitution Series - CTATX



PROJECT: _____
 FIXTURE TYPE: _____
 LOCATION: _____
 CONTACT/PHONE: _____

PRODUCT FEATURES

- Meets State of Connecticut Emergency Building Code (Para. 1011.1.2)
- Extruded Aluminum Enclosure
- Attractive Slim Profile Design
- Face includes "EXIT" wording with the ADA compliant, universal wheelchair accessible symbol
- Charge rate/power "ON" LED indicator light with Test Button
- Maintenance-free NiCad Battery Standard
- Universal Mounting - Ceiling, Back or End Mount
- ETL Listed 90 Minute Emergency run-time, 24 Hour Recharge
- Meets NFPA-101 Life Safety Code
- Exit Face is Illuminated by long-life, high intensity, Red or Green LED's
- Universal Chevron Style Arrow Knockouts
- 120/277V Dual Primary, 60Hz Input
- Standard Finish is White or Black
- 5 Year Warranty



PRODUCT SPECIFICS

INTERNAL SPECIFICATIONS

AC-Only and self-powered versions come standard with high-output LED technology, 120/277VAC input. Self-powered models use nickel cadmium batteries that provide a minimum 90 minutes of emergency duration. Solid state charger and transfer. All models consume 2 Watts or less nominal power.

EXTERNAL SPECIFICATIONS

The CTATX is constructed from durable extruded aluminum. Single, Double or Universal face version must be specified. Universal mounting pattern and key hole slots are stamped into the backplate. Removable chevrons are standard on each fixture. White, baked powder coat finish is standard on all models. External LED monitor light and test switch are standard on self-powered models.

INSTALLATION

Installs in minutes with easy-to-read instructions and detailed diagrams. No special hardware or tools are required.

MODERN DESIGN

The CTATX features a clean look and provides a modern and attractive appearance. The extruded aluminum frame contains no external holes or slots adding to the clean look while eliminating unwanted light leaks. The aluminum also forms a rigid and durable frame that can be securely mounted in any application. The face and back plates are mounted into the frame using a pin and channel system that permits simple and speedy removal during installation.

LIGHT SPECIFICATIONS

Illumination of the CTATX is accomplished utilizing high-intensity, long-life red or green LED's. LED's provide excellent illumination while truly maximizing energy efficiency. As a maintenance-free slution, LED's provide up to 100,000 hours of use without failure.

CODES & STANDARDS

The CTATX is CSA listed and meets or exceeds the following: UL 924, NEC requirements and NFPA 101. Specifically designed to meet the requirements of the State of Connecticut Building Code Paragraph 1011.1.2, ADA Compliant.



	A	B	C
Series			
CTATX	18.5" 469.90mm	7.75" 196.85mm	2" 50.80mm



ORDERING INFORMATION

MODEL	# OF FACES	OPERATION	LETTER COLOR	HOUSING COLOR	OPTIONS
CTATX	1 = Single	A = AC Only	R = Red Letters	W = White	SD = Self Diagnostics
	2 = Double	B = W/ Battery	G = Green Letters	B = Black	BA = Brushed Aluminum
	U = Universal				PK = Pendant Kit (Minimum 6")
					TP = Tamper Proof Screws

Example: CTATX-U-B-R-W-SD