



EC Series

Indoor Industrial Application Emergency



PROJECT: _____
 FIXTURE TYPE: _____
 LOCATION: _____
 CONTACT/PHONE: _____




SPECIFICATIONS: INTERNAL

The EC is configured with 120/277V input and a high-efficiency two stage charger providing precise float voltage control with low voltage disconnect protection. All components used in the circuitry are temperature compensated. Charger status is easily determined via a dual diagnostic LED display. Standard features include low voltage disconnect, AC lockout and brownout protection.

SPECIFICATIONS: EXTERNAL

The EC is constructed with a 20 gauge steel cabinet. Terminal connectors allow for larger gauge wires to be connected for remote loads. The universal mounting pattern stamped into the back of the unit allows for direct mounting to various conduit boxes. Key hole slots are also provided for additional mounting possibilities. Stamped conduit knockouts are supplied standard on all EC units, providing the widest range of options for AC power source connection.

DIMENSIONS



| Unit Size | A | B | C |
|--------------------|----------------------------|----------------------------|---------------------------|
| (6V 18-22W) | 12 ^{1/4"} (311mm) | 5" (127mm) | 3" (76mm) |
| (6V 36W) (12V 36W) | 10" (254mm) | 9" (229mm) | 3 ^{1/4"} (83mm) |
| (6V 42W) (12V 42W) | 13 ^{1/2"} (343mm) | 10 ^{1/8"} (257mm) | 4 ^{1/4"} (108mm) |

NOTE: Cabinet size may vary based on product configuration. Dimension D in drawing above will vary based on heads supplied. First two sizes are 20 gauge steel, the two largest sizes are 18 gauge.



ORDERING INFORMATION

| Series | Operation | Pb-A (Capacity) | Ni-Cd (Capacity) | Emergency Heads | Lamps | Options |
|--------|-----------|-----------------|------------------|---------------------------|--------------------|--|
| EC | 6 (6V) | 18 (6V) | 22 (6V) | 2LR (double PAR36) | See lamp selection | AM (ammeter) |
| | 12 (12V) | 36 (6V, 12V) | 42 (6V, 12V) | 2MRB (double, MR16) | on next page | SD (self diagnostic) |
| | | | | 2SRE (double, LED module) | | CC (custom color- specify) |
| | | | | 0 (no heads) | | CS120 (cord set, 120V only) |
| | | | | | | FAI (fire alarm interface) |
| | | | | | | IRT ² (infrared testing) |
| | | | | | | NC ³ (Ni-Cd) |
| | | | | | | TP (tamper proof screws) |
| | | | | | | TD ⁴ (time delay - specify 5, 10, 15 min) |
| | | | | | | VM (voltmeter) |

NOTE 1: Specify type- open/closed dry contact.
 NOTE 2: HHC (controller for IRT) should be ordered separately.
 NOTE 3: Must select NC from options and indicate wattage/voltage from Ni-Cd column.
 NOTE 4: Must specify at time of order. Specify voltage

EXAMPLE: EC-6-18-2LR9W-SD



EC Series

Indoor Industrial Application Emergency



PROJECT: _____
 FIXTURE TYPE: _____
 LOCATION: _____
 CONTACT/PHONE: _____

EMERGENCY HEADS

The EC is supplied standard with two (2) top mounted LR PAR36 style heads with 9W incandescent lamps. MRB style heads with LED MR16 lamps and SRE LED module heads are optional. Lamp heads can be mounted either on the top or on the sides of the unit allowing for up to four (4) heads to be mounted on the largest units (2 top, 2 side or 3 on top). The lamp head styles are constructed of high impact thermoplastic in a color matching the finish of the cabinet (white is standard). Both head types feature a unique twist locking collar that securely holds the lens and facilitates quick and easy re-lamping.

SPECIFICATIONS: ELECTRICAL

BATTERY: The EC is designed with a maintenance free, sealed valve regulated lead acid battery that provides a minimum emergency duration of 90 minutes (for the listed rating). Recharge time of the battery is 24 hours. An optional Nickel-Cadmium battery is available.

SPECIFICATIONS: MECHANICAL

Remote lamp loads are connected to the emergency power supply with sturdy terminal connectors. These connectors allow for a large gauge of wire to be used increasing the flexibility of installation. The EC is supplied standard in a durable white powder coat, baked finish. Other colors are available, including custom color matching, please specify.

SELF-DIAGNOSTIC

The Mule Self-Diagnostic system (optional) performs one 5 minute discharge test monthly. Every 6 months two 90 minute discharge tests are performed. This tests both full battery capacity and recharge capability, as required by the fire code. The information is communicated simply and intuitively to maintenance personnel via a single multi-color LED. The Mule Self-Diagnostic system also includes 0, 5, 10 or 20 minute time delay function to allow HID lighting to restrike. IRT one button press tests unit for 90 minutes per code.

WARRANTY

The EC comes with a 3-year factory warranty. Lamps are not covered under the warranty. Deliberate damage, misuse, improper installation effectively cancel the warranty.

LAMP SELECTION

| | 6V | 12V |
|--------------|-------|----------|
| Incandescent | 9W | 9W |
| MR16 LED | 5, 7W | 2, 5, 7W |
| LED Module | 3, 4W | 3, 4W |

MODEL RATING GUIDE PB-A (CAPACITY)

| Model | Input Voltage | Wattage Rating 90 Minutes |
|----------|---------------|------------------------------|
| EC-6-18 | 6 | 18 |
| EC-6-36 | 6 | 36 |
| EC-12-36 | 12 | 36 |

MODEL RATING GUIDE NI-CD (CAPACITY)

| Model | Input Voltage | Wattage Rating 90 Minutes |
|----------|---------------|------------------------------|
| EC-6-22 | 6 | 22 |
| EC-6-42 | 6 | 42 |
| EC-12-42 | 12 | 42 |