EGX Series - Thermoplastic

Thermoplastic Housing Self-Luminous Signs

PROJECT:
FIXTURE TYPE:
LOCATION:
CONTACT/PHONE:



LIGHTING

• 100% Reliable: Internally illuminated by sealed tritium gas light sources.
• Requires no electrical power, wiring or batteries, and no maintenance.
• Green light output for maximum visibility in dark conditions. No external light or power is required for activation.
• Lamps guaranteed for up to 20 years of continuous operation.
• Observation tested for visibility up to 125 ft in complete darkness.

CONSTRUCTION

• One-piece flameproof thermoplastic injection molded housing only 1" thick.
• Universal field adjustable chevron arrows and universal mounting brackets.
• Standard finishes satin white or black housing, with white lettering and high contrast red, green or black faceplate. Optional finishes include custom colors.
• No visible mounting hardware.
• Suitable for use in hazardous atmospheres and wet locations.

DISPOSAL

• We will accept returns for proper disposal. It is unlawful to abandon or dispose of self-luminous signs except by transfer to persons specifically licensed by the nuclear regulatory agency or by an agreement state.

CODES & APPROVALS

• Manufactured and tested to UL Standard 924 and Life Safety Code NFPA 101 and of National Electrical Code Article 500, Class I and II conditions. Sealed source and device registered with USNRC for distribution to general licenses.

WARRANTY

• Unconditional warranty is provided for illuminated life as specified on the product label.

DESIGNED & MADE IN THE USA

Intertek
CONFORMS TO UL 924/ CSA 22.2 #141

ORDERING INFORMATION

Model	Useful Life	No. of Faces	Face Color	Housing Color	Options/Accessories
EGX	10 = 10 Years	1 = 1	R = Red	W = White	PEN = Pendant Mount Kit (12" Standard)
	20 = 20 Years	2 = 2	G = Green	B = Black	CAN = Canopy Mount Kit
			"Color" = Custom Color	"Color" = Custom Color	PSC = Polycarbonat Security Cover
					REC = Recessed Mount Kit Aluminum
					ASH = Security Housing
					SLCC = Special Lettering-Graphics

EXAMPLE: EGX-10-1-G-B-PEN

EGX Series - Thermoplastic

Thermoplastic Housing Self-Luminous Signs

PROJECT:
FIXTURE TYPE:
LOCATION:
CONTACT/PHONE:

SUGGESTED SPECIFICATIONS

Supply and install Mule Lighting, Inc EGX Series self luminous EXIT signs illuminated by tritium gas lamps. The housing shall be fabricated from thermoplastic with overall dimensions of 13 5/16" x 8 1/4" x 1", having a minimum UL flame rating of 94V-0, minimum external wall thickness of .09" and a polycarbonate window of .125" minimum thickness. Universal mounting brackets shall be supplied. For signs specified with a luminous life of 10 years, the minimum initial brightness measured at any point on the surface shall be 0.12 ft L (.21 cd/m); for any other specified lifetime, the minimum surface brightness shall be 0.012 ft L (.021 cd/m) per year of specified luminous life.

OPTIONS & ACCESSORIES

Description	Code
Pendant Mount Kit	PEN
Canopy Mount Kit	CAN
Polycarbonat Security Cover	PSC
Recessed Mount Kit Aluminum	REC
Security Housing	ASH
Special Lettering-Graphics	SLCC

MOUNTING DATA & DIMENSIONS

