

BENEFITS & FEATURES

- Architectural-grade, die cast aluminum housing and faceplate
- Includes die cast aluminum canopy for top or end mounting
- Universal mounting pattern knockouts for J-box mounting
- Pre-drilled canopy attachment locations with easily removed hole covers
- Integral wiring channels
- Gently curved faceplate snaps into housing without tools
- Second faceplate included to field-convert from single to double face with universal configuration
- 8" letters with 1" stroke width
- Full-size, 3/4" wide chevron directional indicators are field selectable
- Optional Self-Test and Self-Diagnostics (battery backup version only)
- Dual voltage 120/277VAC
- Maintenance-free 4.8V sealed, nickel cadmium battery (battery backup version)


CODE COMPLIANCE

- UL Listed
- NFPA 101 Life Safety Code compliant
- NEC and OSHA compliant
- New York City Approved

DIE CAST ALUMINUM LED EXIT

The New York Approved NY Meridian Series is ideal for applications that require the durability of metal construction in an economical package. All NY Meridian Series signs include a second faceplate for universal single/double face applications and canopy for universal top, end or back mounting.





ACCESSORIES

Catalog Number	Description		
BG-1	Polycarbonate Vandal Shield - Large		
WG-1	Wire Guard - Small		
	separately. To order, specify catalog number. Refer to		

Options & Accessories specification sheet for additional information.

ORDERING INFORMATION

MODEL	OPERATION	# OF FACES	LETTER COLOR	HOUSING COLOR	OPTIONS
NYMD	A = AC-Only	1 = Single	R = Red	BA = Black w/ Brushed Aluminum	SD = Self-Diagnostics
	B = Battery Back-Up	2 = Double		BB= All Black	-
		U = Universal		WH = All White	
Ordering Exam	ple: NYMD-B-2-R-BA-SD			AA = All Aluminum	