



CATALOG NUMBER:

NOTES:

FIXTURE TYPE:

PROJECT:

The Patriot HZ REMOTE is vandal resistant, durable and can be depended on in the event of an emergency. The gasketed die-cast aluminum housing and clear polycarbonate lens is suitable for areas that are wet, cold or that generate dust. Tamper resistant screws are standard and ensure the integrity of the remote. Performance optics allows up to 70 foot spacing on center. The Patriot series is approved for use in Class I Division 2, Groups A-D, Class II Divisions 1& 2, Groups E-G: T coded T4A, T3B, T3A, T2D, T2A, or T1.



■ Specifications: External

The Patriot HZ REMOTE is constructed from a durable, fully gasketed NEMA 4X and IP66 rated die-cast aluminum housing. Stainless steel mounting straps are supplied for surface mounting. The Patriot HZ REMOTE is supplied standard in a durable gray powder coat, baked finish. Other colors are available, including color matching, please specify. CSA 22.2 No. 141 Performance Certified.

■ Dimensions

■ Product Features

The Patriot HZ REMOTE is a hazardous rated industrial emergency unit that is offered in 6V, 12V and 24V configurations. Features a hazardous approved conduit fitting.




Installation: The Patriot HZ REMOTE can be surface wall or ceiling mounted.

The Patriot HZ remote is approved for use in Class 1 Division 2, Groups A, B, C, D; Class 2 Divisions 1 & 2, Groups E, F, G: T coded T4a, T3B, T3a, T2d, T2a, or T1.

Applications: The Patriot HZ remote is ideal for industrial refrigeration, bottling facilities, rendering plants, refineries, gasoline storage, dry cleaning plants, spray finishing areas, aircraft hangars, fuel servicing areas, hazardous areas and food service areas.

Housing: Fully gasketed die-cast aluminum construction with an impact resistant polycarbonate lens. Stainless steel mounting feet and hardware.

MR16 or optional MR16 LED lamps provide reliability and performance with up to 70 foot spacing on center.



Series	A"	B"	C"
PTR-HZ	16.25"	7.5"	6"
	413mm	191mm	152mm

■ Ordering Logic

Series	Operation	Lamp Type	Options
RMT-PTR-HZ	6 (6V)	See lamp selection	* WG (wireguard)
	12 (12V)	guide on next page	
	24 (24V)		

■ Ordering Example: RMT-PTR-HZ-12-MR16-10W

Hazardous / IP66 / NEMA 4x /
vandal resistant / sanitation / cold





CATALOG NUMBER:

NOTES:

FIXTURE TYPE:

PROJECT:

■ Tamper Resistant Design

The Patriot HZ REMOTE series of vandal resistant emergency lighting units are designed to stand up to abuse in applications such as schools, public areas, institutions and apartment complexes where vandalism may potentially occur. The heavy die-cast aluminum body and polycarbonate lens offer extreme protection and superior performance. Tamper resistant screws are standard and ensure the integrity of the unit.

■ Sanitation Listed (SL)

The Patriot HZ REMOTE is sanitation approved. The Intertek verified splash zone listing is equivalent to the NSF Standard 2, meeting the rigorous sanitation, electrical safety and performance standards of food service environments.

■ Hazardous

The Patriot HZ UNIT is approved for use in Class 1 Division 2, Groups A, B, C, D; Class 2 Divisions 1 & 2, Groups E, F, G: T coded T4a, T3B, T3a, T2d, T2a, or T1.

■ Temperature Codes

Temperature Codes Class 1, Div. 1

Lamp	10W Hal.	12W Hal.	20W Hal.	7W LED max
T Code	T3A	T3B	T2D	T4A

Temperature Codes Class 2, Div. 1 & 2

Lamp	10W Hal.	12W Hal.	20W Hal.	7W LED max
T Code	T4A	T4A	T4A	T4A

■ Lamp Selection

	6V	12V	24V
MR16	5, 10W	10, 12, 20, 35, 50W	12, 20, 35, 50W
LED	5, 7W	5, 7W	5, 7W

■ Warranty

The Patriot HZ UNIT comes with a 3-year factory warranty. Deliberate damage, misuse, improper installation effectively cancel the warranty.