



# SQ-LED Series

ALL LED THERMOPLASTIC EMERGENCY LIGHT



PROJECT: \_\_\_\_\_  
 FIXTURE TYPE: \_\_\_\_\_  
 LOCATION: \_\_\_\_\_  
 CONTACT/PHONE: \_\_\_\_\_

## PRODUCT DESCRIPTION

The SQ-LED Series thermoplastic LED Emergency Light offers contemporary aesthetics, quick installation and premium features such as LED lamps, High Lumen Output and Self-Diagnostic versions all in an economical package.

## PRODUCT SPECIFICATIONS

### construction

Injection molded, engineering-grade, UV-stable thermoplastic • UL94V-0 flame rating • Impact, scratch, fade and corrosion-resistant • Snap-fit housing and mounting plate • Universal mounting plate with quick-connect feature • White or black textured finish.

### electrical

Dual 120/277 voltage standard • Rated for use in damp locations • Solid state charging and switching • Brownout protection • Battery low voltage disconnect • Overload and short circuit protection • Low-profile, integrated test switch and AC indicator light.

### lamps

Long life, energy saving LED lamps • 1W per head (8 LED's per head total)

### heads

Includes two 1W white LED lighting heads • Contemporary semi-recessed round head design • High performance chrome-plated metallized reflector and plastic lens for optimal light distribution • Track-and-swivel arrangement permits full range of direction of lamp head adjustment • High-lumen option available for increased center-to-center spacing.

### battery


Maintenance-free sealed NiCad battery • Standard battery will operate fixture for a minimum of 90 minutes in the event of a power outage

### code compliance

UL924 • UL Listed for damp locations (0°C – 50°C) • NFPA 101 Life Safety Code compliant • NEC and OSHA compliant • Meets the State of Minnesota energy efficiency requirements • CEC Title 20 Compliant

### warranty

5-year warranty. Product specifications subject to change without notice.



## ENGINEERING DATA

Input Voltage	Max. Amps	Max. Watts
120	0.04	2.0
277	0.02	2.0

## INSTALLATION

### mounting

Suitable for wall or ceiling mounting • Surface mount via easy connect back plate, which fits most standard junction boxes and snaps into place making internal electrical connections



## ORDERING INFORMATION

model	housing color	options	accessories
SQ-LED	W = White B = Black	SD = Self Diagnostics HL <sup>1</sup> = High Lumen Heads (1.5W)	BGR-1 = Polycarbonate Vandal Shield WWG-1 = Wire Guard (wall mount-white) BPG5 = Wire Guard (White Powdercoat Finish)

### Notes

<sup>1</sup>12-LED (1.5W) per head provides increased center-to-center spacing

Ordering Example SQ-LED-W-SD



# SQ-LED Series

ALL LED THERMOPLASTIC EMERGENCY LIGHT




PROJECT: \_\_\_\_\_  
FIXTURE TYPE: \_\_\_\_\_  
LOCATION: \_\_\_\_\_  
CONTACT/PHONE: \_\_\_\_\_


## SPACING DIAGRAMS

### SQ-LED

3ft Path Spacing




6ft Path Spacing



### SQ-LED-HL

3ft Path Spacing



6ft Path Spacing

