



CEM-USA

Reduced Profile All LED Exit & Emergency Thermoplastic Combo



PROJECT:


FIXTURE TYPE:

LOCATION:

CONTACT/PHONE:



DIMENSIONS



ILLUMINATION

- Ultra-bright, energy efficient, long-life Red or Green LED EXIT sign illumination.
- Ultra-bright, energy efficient, long-life White LED adjustable LED lamp heads provide up to 30-ft center-to-center spacing with 3-ft path of egress at 10-ft mounting height.
- 1.5 watt (3 LEDs x 0.50 watt) per head.
- Unique all-inclusive lamp, reflector and lens assembly.

ELECTRICAL

- Dual 120/277 voltage.
- Unique bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check battery).
- Charge rate/power "ON" LED indicator light and push-to- test switch for mandated code compliance testing.
- 3.6V long life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

HOUSING

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.
- Snap-out Chevron directional indicators.

OPTIONS

- RC: Remote capacity of 2.5 watts.
- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and life safety codes. Universal 120-277 voltage

WARRANTY

- Five-year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C – 50°C).
- Certified to CEC under Title 20 Regulations.
- USA: Substantial transformation assembly in U.S. complies with "Assembled in USA" under the Buy American Act.



ORDERING INFORMATION

Model	No. of Faces	Letter Color	Housing Color	Options
CEM-USA	Universal Single/	R= Red	W = White	RC = Remote Capacity
	Double Face	G = Green	B = Black	SDT = Self-Diagnostics

Ordering Example: CEM-USA-R-W



CEM-USA

Reduced Profile All LED Exit & Emergency Thermoplastic Combo



PROJECT: _____
FIXTURE TYPE: _____
LOCATION: _____
CONTACT/PHONE: _____

ELECTRICAL INFORMATION

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)	
	120V	277V	120V	277V
CEM RED/GREEN	1.2	1.2	0.12	0.11
CEM RED/GREEN RC	1.2	1.2	0.12	0.11
CEM RED SDT	2.7	2.7	0.32	0.32
CEM GREEN SDT	2.4	2.4	0.29	0.29
CEM RED/GREEN RC SDT	3.0	3.0	0.40	0.40

REMOTE LAMP COMPATIBILITY

MODEL NUMBER	BATTERY	REMOTE CAPACITY	COMPATIBLE REMOTE HEAD FAMILY			
			RHLED	MRHLED	RH16LED	SRHLED
CEM RC	3.6V	2.5W	X	X		