

U-MD Series

PROJECT:

FIXTURE TYPE: LOCATION:

THE ULTIMATE DIECAST SERIES



* Manual Test/Self-Diagnostics

ELECTRICAL

• 120 to 277VAC universal voltage, 50/60Hz.


* AC-Only/Battery Backup Switchable

- Recharge time 24 hours, emergency runtime more than 90 minutes, lithium iron phosphate battery.
- Trickle charge after battery fully charged.
- Battery discharge protection.

* Red/Green Switchable

- Solid-State transfer circuit.
- Test Switch / Charge Indicator light.

DIMENSIONS



CONFIGURATION

- Die cast aluminum housing, compact and decorative design.
- Single and double face universal package.
- EXIT letter 6" height and 3/4"stroke, with knockout chevron directional arrows.
- Red and Green LED color changeable, red and green diffuser changeable.

ILLUMINATION

- Field selectable Red or Green sign with matched color diffuser.
- Default setting at factory is red color

UNIVERSAL ATTRIBUTES

- Self-testing and self-diagnostics is standard, can switch to manual test function if application requires.
- Battery backup version can switch to AC only version in the field.

MOUNTING

- Suitable for wall mounting, ceiling mounting and end mounting.
- Universal J-Box mounting pattern on back plate.
- Canopy provided for ceiling & end mounting.

CODE COMPLIANCE

- UL listed and meets or exceed all requirement in NFPA 70, NFPA 101 life safety code.
- Self-Contained version suitable for 5°C 50°C.
- AC only version suitable for -25°C 50°C.
- Suitable for damp location.
- Compliant CEC title 20 efficiency regulation.









ORDERING INFORMATION

Model	Description
U-MD-U-BAB	Ultimate DieCast EXIT, Single/Double Face, RED/Green Switchable, Battery/AC-Only Switchable, Self-Diagnostics/Manual Test Switchable, Black with Brushed Aluminum Finish
U-MD-U-WW	Ultimate DieCast EXIT, Single/Double Face, RED/Green Switchable, Battery/AC-Only Switchable, Self-Diagnostics/Manual Test Switchable, All White Finish
U-MD-U-BAB-REM	Ultimate DieCast EXIT, Single/Double Face, RED/Green Switchable, Battery/AC-Only Switchable, Self-Diagnostics/Manual Test Switchable, Black with Brushed Aluminum Finish/ 1.5 Watt remote Capability

ORDERING EXAMPLE: U-MD-U-BAB



U-MD Series

	<u>P</u>
	F
CZ	Ī
SPEC	(

PROJECT: FIXTURE TYPE:

LOCATION: CONTACT/PHONE:

THE ULTIMATE DIECAST SERIES

MODEL LIST & ELECTRICAL RATING

No.	Туре	Letter Test Color Facility			Recharge Time	Emergency Run time	Input Rating				Output Rating	
			Test Facility	Battery			Vac	Hz	mA	w	Integral	Remote Capability
1	Battery	Red/Green Universal	Self-testing Self-diagnostics	LiFePO ₄ 3.2V400mAh	24 hours	90 minutes	120-277	50/60	22	1.2	0.3W	/
2	AC-Only	Red/Green Universal	/	/	/	/	120-277	50/60	22	1.2	0.3W	/